

# INGERSOLL RAND NEXT GENERATION R SERIES

## OIL FLOODED ROTARY SCREW AIR COMPRESSORS

Ingersoll Rand works to keep you ahead of your competition with Next Generation R-Series air compressors that lower total cost of ownership through high-quality components, industry leading energy efficiency and global expertise.



### WORLD-CLASS PERFORMANCE

#### → DESIGNED FOR SIGNIFICANTLY IMPROVING EFFICIENCY

with state-of-the-art air ends, IE3/ NEMA Premium® high-efficiency motor, a free-floating cooling system and optional Energy Recovery System (ERS) significantly improve efficiency

#### → V-SHIELD™ TECHNOLOGY

provides a totally integrated, leak-free design featuring PTFE stainless steel braided oil hoses and O-ring face seals

#### → XE-SERIES CONTROLLER

delivers increased control functionality through an intuitive user interface as well as remote access with any common, current web browser



#### → PROGRESSIVE ADAPTIVE CONTROL (PAC™)

monitors key operating parameters and continuously adapts to prevent unexpected downtime

#### → ENHANCED SERVICEABILITY ENSURES

increased uptime with features such as two-stage filtration, easy maintenance and Ingersoll Rand premium grade coolant

#### → HINGED-DOOR SERVICE ACCESS

with integrated handles provides quick, easy access to all user-maintainable components

#### → OPTIONAL TOTAL AIR SYSTEM (TAS)

provides clean, dry air in a single package that minimizes installation costs, reduces footprint and improves ISO air quality

STANDARD FEATURES INCLUDE:	OPTIONAL FEATURES INCLUDE:
Premium performance airend	Total Air System (TAS) package with integrated air dryer
Energy saving, intuitive Xe-90M Series controller with remote access	XE 145M Controller with a 145mm screen
Air-cooled free-floating cooling system with moisture separator	Low ambient temp. protection as low as -23°C (-10°F)
PAC™ protection adjusts operating parameters in response to compressor operation	Outdoor modification/rain protection
V-Shield™ stainless steel piping, vibration isolation, PTFE hoses, leak-free connections	Premium high dust filtration
Noise attenuation enclosure with hinged removable doors	Water-cooled system
Control panel protection and soft starter	Flow control inlet modulation
Star-delta reduced voltage starter and premium TEFC motor	Phase monitor protection
Package rated for 46°C (115°F) ambient operation	

## TECHNICAL SPECIFICATIONS

STANDARD 50 HZ PERFORMANCE					
Model	Max Pressure	Nominal Power	Capacity	Weight Air Cooled	Weight Water-Cooled
	barg	kW	m3/min	Kg	Kg
RS45i	7.5	45	8.9	1,841	1746
RS45i	8.5	45	8.3	1,841	1746
RS45i	10.0	45	7.7	1,841	1746
RS45i	14.0	45	5.9	1,841	1746
RS55i	7.5	55	11.2	1,936	1841
RS55i	8.5	55	10.4	1,936	1841
RS55i	10.0	55	9.3	1,936	1841
RS55i	14.0	55	7.4	1,936	1841
RS75i	7.5	75	14.5	1,962	1867
RS75i	8.5	75	13.9	1,962	1867
RS75i	10.0	75	13.0	1,962	1867
RS75i	14.0	75	10.7	1,962	1867

TOTAL AIR SYSTEM (TAS) 50 HZ PERFORMANCE					
Model	Max Pressure	Nominal Power	Capacity	Weight Air Cooled	Weight Water-Cooled
	barg	kW	m3/min	Kg	Kg
RS45i	7.0	45	8.9	1,994	1899
RS45i	8.0	45	8.3	1,994	1899
RS45i	9.5	45	7.7	1,994	1899
RS55i	13.5	45	5.9	1,994	1899
RS55i	7.0	55	11.2	2,089	1994
RS55i	8.0	55	10.4	2,089	1994
RS55i	9.5	55	9.3	2,089	1994
RS75i	13.5	55	7.4	2,089	1994
RS75i	7.0	75	14.5	2,115	2020
RS75i	8.0	75	13.9	2,115	2020
RS75i	9.5	75	13.0	2,115	2020
RS75i	13.5	75	10.7	2,115	2020



**DIMENSIONS (L x W x H)**  
2,433mm x 1,250mm x 2,032mm